

## CLAIMS

Please cancel claims 13 and 35.

Please amend claims 1, 14, 23, and 36 to read as follows:

1. (Currently Amended) thod of allocating resources in a network, comprising:

accessing data from a fixed wireless loop network having a plurality of stations which are each associated with a plurality of remote units, each-at least a portion of the plurality of remote units being capable of receiving communication services from more than one of the plurality of stations, but assigned to receive communication service from the association station;

comparing communication service load data associated with one or more stations to a communication load criteria to identify a potentially overloaded station;

identifying at lest one of the plurality of remote units assigned to the potentially overloaded station as re-assignable to a substitute station; and

reducing-reassigning the identified remote units to the substitute station to thereby reduce the number of remote units assigned to receive communication service from the potentially overloaded station.

2. (Original) The method of claim 1, wherein the fixed wireless loop network is a hypothetical network.

3. (Original) The method of claim 1, wherein the data from the fixed wireless loop network includes data from a service area plot.

4. (Original) The method of claim 3, wherein the service area plot is a service area plot for a hypothetical network.

5. (Original) The method of claim 3, wherein the service area plot is a corrected service area plot.

6. (Original) The method of claim 3, wherein the service area plot is a best server plot.

7. (Original) The method of claim 3, wherein the service area plot is a best interference plot.

8. (Original) The method of claim 3, wherein the service area plot is divided into bins.

9. (Original) The method of claim 1, wherein the communication service load data includes a level of communication service load projected for a future date.

10. (Original) The method of claim 1, wherein the communication service load data includes an approximate level of communication service for a peak usage time.

11. (Original) The method of claim 1, wherein comparing communication service load data from one or more stations to communications load criteria includes comparing the communication service load data to a communication service load threshold.

12. (Original) The method of claim 8, wherein the communication service load threshold is the communication service capacity of the potentially overloaded station.

13. (Canceled)

14. (Currently Amended) The method of claim ~~13~~1, wherein reducing the number of remote units receiving communication service from the potentially overloaded station includes applying re-assignment criteria to the re-assignable remote unit to determine whether the re-assignable remote unit can be re-assigned to the substitute station.

15. (Original) The method of claim 14, wherein applying the reassignment criteria includes determining whether re-assigning the re-assignable remote unit to the substitute station would cause the substitute station to become a potentially overloaded station.

16. (Original) The method of claim 14, wherein applying the reassignment criteria includes comparing a strength of a signal from the substitute station against a signal strength threshold.

17. (Original) The method of claim 14, wherein applying the reassignment criteria includes comparing the strength of an interference signal experienced by the substitute station to an interference threshold.

18. (Original) The method of claim 14, wherein applying the reassignment criteria includes comparing a strength of a signal from the substitute station against a signal strength threshold and determining whether re-assigning the re-assignable remote unit to the substitute station would cause the substitute station to become a potentially overloaded station.

19. (Original) The method of claim 14, wherein applying the reassignment criteria includes comparing a strength of a signal from the substitute station against a signal strength threshold and comparing the strength of an interference signal experienced by the substitute station to an interference threshold.

20. (Original) The method of claim 14, wherein applying the reassignment criteria includes determining whether re-assigning the re-assignable remote unit to the substitute station would cause the substitute station to become a potentially overloaded station and comparing the strength of an interference signal experienced by the substitute station to an interference threshold.

21. (Original) The method of claim 14, wherein applying the reassignment criteria includes determining whether re-assigning the re-assignable remote unit to the substitute station would cause the substitute station to become a potentially overloaded station, comparing the strength of an interference signal experienced by the substitute station to an interference threshold, and comparing a strength of a signal from the substitute station against a signal strength threshold.

22. (Previously Presented) The method of claim 1, further comprising:  
creating a service area plot which accounts for remote units re-assigned from one station to a substitute station.

23. (Currently Amended) A signal bearing medium including machine readable instructions executable by a processing apparatus to perform a method of allocating resources in a network, the method comprising:

accessing data from a fixed wireless loop network having a plurality of stations which are each associated with a plurality of remote units, ~~each~~ at least a portion of the plurality of remote units being capable of communicating with the associated station and a substitute station, but assigned to receive communication service from the associated station;

comparing communication service load data associated with one or more stations to a communications load criteria to identify a potentially overloaded station;

identifying at least one of the portion of remote units as re-assignable to the substitute station; and

~~reducing~~ reassigning the identified remote units to the substitute station to thereby reduce the number of remote units assigned to receive communication service from the potentially overloaded station.

24. (Previously Presented) The medium of claim 23, wherein the fixed wireless loop network is a hypothetical network.

25. (Previously Presented) The medium of claim 23, wherein the data from the fixed wireless loop network includes data from a service area plot.

26. (Original) The medium of claim 25, wherein the service area plot is a service area plot for a hypothetical network.

27. (Original) The medium of claim 25, wherein the service area plot is a corrected service area plot.

28. (Original) The medium of claim 25, wherein the service area plot is a best server plot.

29. (Original) The medium of claim 25, wherein the service area plot is a best interference plot.

30. (Original) The medium of claim 25, wherein the service area plot is divided into bins.

31. (Original) The medium of claim 23, wherein the communication service load data includes a level of communication service load projected for a future date.

32. (Original) The medium of claim 23, wherein the communication service load data includes an approximate level of communication service for a peak usage time.

33. (Original) The medium of claim 23, wherein comparing communication service load data from one or more stations to a communications load criteria includes comparing the communication service load data to a communication service load threshold.

34. (Original) The medium of claim 33, wherein the communication service load threshold is the communication service capacity of the potentially overloaded station.

35. (Canceled)

36. (Currently Amended) The medium of claim ~~35~~ 23, wherein reducing the number of remote units receiving communication service from the potentially overloaded station includes applying a re-assignment criteria to the re-assignable remote unit to determine whether the re-assignable remote unit can be re-assigned to the substitute station.

37. (Original) The medium of claim 36, wherein applying the reassignment criteria includes determining whether re-assigning the re-assignable remote unit to the substitute station would cause the substitute station to become a potentially overloaded station.

38. (Original) The medium of claim 36, wherein applying the reassignment criteria includes comparing a strength of a signal from the substitute station against a signal strength threshold.

39. (Original) The medium of claim 36, wherein applying the reassignment criteria includes comparing the strength of an interference signal experienced by the substitute station to an interference threshold.

40. (Original) The medium of claim 36, wherein applying the reassignment criteria includes comparing a strength of a signal from the substitute station against a signal strength threshold and determining whether re-assigning the re-assignable remote unit to the substitute station would cause the station to become a potentially overloaded station.

41. (Original) The medium of claim 36, wherein applying the reassignment criteria includes comparing a strength of a signal from the substitute station against a signal strength threshold and comparing the strength of an interference signal experienced by the substitute station to an interference threshold.

42. (Original) The medium of claim 36, wherein applying the reassignment criteria includes determining whether re-assigning the re-assignable remote unit to the substitute station would cause the substitute station to become a potentially overloaded station and comparing the strength of an interference signal experienced by the substitute station to an interference threshold.

43. (Original) The medium of claim 36, wherein applying the reassignment criteria includes determining whether re-assigning the re-assignable remote unit to the substitute station would cause the substitute station to become a potentially overloaded station, comparing the strength of an interference signal experienced by the substitute station to an interference threshold, and comparing a strength of a signal from the substitute station against a signal strength threshold.

44. (Original) The medium of claim 23, wherein the method further comprises:

creating a service area plot which accounts for remote units reassigned from one station to a substitute station.